



## PRODUCT DATA SHEET

### GIANT AIR TOOL OIL

Premium Hydrocracked Refined Mineral Pneumatic Air Tools Oil

#### DESCRIPTION

GIANT AIR TOOL OIL is a premium product formulated to lubricate the relevant internal parts of both piston and rotary types of pneumatic Air Tools. The oil is formulated from refined hydrocracked base stocks treated with special additives to prevent rust, sludge, varnish, acids, air-foaming, while protecting moving parts from wear, thus resulting in excellent sustained speed and power in the air tools. The oil also contains demulsifying additives to handle water that is formed during condensation.

GIANT AIR TOOL OIL is compatible with most common pumps, valves, and seal materials found in pneumatic air tools.

#### BENEFITS

- Meets or exceeds lubrication requirements of all types of rotary and piston pneumatic air tools.
- Exceptional anti-wear, anti-foam and demulsibility additives.
- Keeps parts clean and in good condition by preventing rust, sludge, varnish and acids from forming.
- Compatible with pumps, seals and valves commonly used in pneumatic air tools.

#### PERFORMANCE STANDARDS

- ISO VG 32

#### TYPICAL APPLICATIONS

- Rotary and Piston types of pneumatic air tools.

#### TYPICAL PROPERTIES

<b>ISO VG</b>	<b>32</b>
Specific Gravity	0.868
Kinematic Viscosity, cSt @ 40°C	31.0
Kinematic Viscosity, cSt @ 100°C	5.6
Viscosity Index	120
Pour Point, °C	-21
Flash Point, °C	210