



GIANT HYDRAULIC JACK OIL

Premium Hydrocracked Refined Mineral Hydraulic Jack Oil

DESCRIPTION

GIANT HYDRAULIC JACK OIL is formulated from refined hydrocracked base stocks for standard hydraulic, jack and hoist systems including those with vane, piston, gear or vacuum pumps. The oil contains additives to prevent rust, sludge, varnish, acids, air-foaming, as well as additives for anti-wear and demulsibility.

GIANT HYDRAULIC JACK OIL is compatible with most common pumps, valves, and seal materials found in standard hydraulic, jack and hoist systems.

BENEFITS

- Meets or exceeds lubrication requirements of all types of standard hydraulic, jack and hoist systems.
- Exceptional anti-wear, anti-foam and demulsibility additives.
- Keeps parts clean and in good condition by preventing rust, sludge, varnish and acids from forming.
- Compatible with pumps, seals and valves commonly used in standard hydraulic, jack and hoist systems.

PERFORMANCE STANDARDS

- ISO VG 32
- DIN 51524, Part II & III
- Vickers M-2950-S (Mobile Equipment) & Vickers I-286- S (Industrial Equipment)
- AFNOR NF E 48-603 (HM)
- DENISON HF-2, HF-1, HF-0
- US Steel 127, 136
- Cincinnati Milacron P-68, P-69 & P-70

TYPICAL APPLICATIONS

Standard hydraulic, jack and hoist systems including those with vane, piston, gear or vacuum pumps.

TYPICAL PROPERTIES

ISO VG	32
Specific Gravity	0.868
Kinematic Viscosity, cSt @ 40°C	31.0
Kinematic Viscosity, cSt @ 100°C	5.6
Viscosity Index	120
Pour Point, °C	-21
Flash Point, °C	210