



GIANT TWO STROKE

Motor Oil for High Performance Air-Cooled 2-Cycle Engines

DESCRIPTION

GIANT TWO STROKE motor oil has been developed to meet the demands of modern high performance air-cooled two-cycle engines.

The technology utilized in GIANT TWO STROKE provides exceptional performance for a mineral oil based two-stroke product, using the latest additive technology with high viscosity index.

GIANT TWO STROKE is fully compatible with all common elastomer seals, preventing problems commonly encountered through oil leakage and power loss, and is recommended for both leaded and unleaded fuels. It is not recommended in two-stroke Outboard engines.

PERFORMANCE STANDARDS

- JASO FC
- API TC

BENEFITS

- Protects engines at peak high RPMs and temperatures.
- Achieves maximum engine power and efficiency through clean-burning.
- Reduces port engine deposits, prevents spark plug fouling, ring sticking, piston deposits, piston seizure and is readily soluble in gasoline.
- Excellent combustion characteristics and outstanding low smoke performance. Advanced additives burn cleanly, significantly reducing exhaust smoke and prevents exhaust port blocking.
- Excellent protection reduces wear and hard deposits.
- Maintains operational efficiency and extends engine life.
- Compatible with all common elastomer seal

TYPICAL APPLICATIONS

GIANT TWO STROKE is designed for use in all types of air-cooled 2-stroke motorcycles, scooters, lawn mowers, chain saws, mopeds, portable power equipment, etc.

TYPICAL PROPERTIES

SAE Grade	20
Density @ 15 °C kg/L	0.8728
Kinematic Viscosity, mm ² /s @ 40°C	71.4
Kinematic Viscosity, mm ² /s @ 100°C	9.0
Viscosity Index	119
Pour Point, °C	-29
Flash Point, °C	>220