



Material Safety Data Sheet
GIANT BLUE PREMIX

Rev: 00
Date: 11/08/2021

Section 1: Chemical and Company Identification

Product Name/Identifier GIANT BLUE PREMIX
Company Information Central Auto Parts and Equipment Limited
 84 Armstrong Street, Palmerston North
 New Zealand
Emergency Telephone (64) 6-3535200
Fax Number (64) 6-3535201

Section 2: Hazards Identification

GHS CLASSIFICATION

| Health | Environmental | Physical |
|---|----------------|---|
| Reproductive Toxicity (Unborn Child) Cat 2 | Not Classified | H361D – Suspect of damaging the unborn child |
| Acute Toxicity (Oral) Cat 4 | | H302 – Harmful if swallowed |
| Specific Target Organ Toxicity Cat 2 - Repeated Exposure (Kidney) | | H373 – May cause damage to organs (kidney) through prolonged or repeated exposure |

Hazard Summary: Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure. Possible reproductive hazard. Occupational exposure to the substance or mixture may cause adverse health effects.

GHS LABEL:

Label according to Regulation (EC) No. 1272/2008 as amended
Contains: Ethylene glycol, Sodium 2-ethylhexanoate



Signal Word: Warning

Hazard Statements

H302 Harmful if swallowed.
H361D Suspect of damaging the unborn child.
H373 May damage to organs (kidney) through prolonged or repeated exposure.

Prevention Precautionary Statements

P102 Keep out of reach of children.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor

Storage Precautionary Statements

P405 Store locked up.

Disposal Precautionary Statements

P501 Dispose of contents/container in accordance with local / regional / national / international regulations.

Supplemental label information: None

Other Hazards

Not a PBT or vPvB substance or mixture.

Section 3: Compositions / Information on Ingredients

| Chemical Identity | Weight % | CAS# | Reach Registration No. | Index No. | Notes |
|-------------------------|----------|-------------------------|---------------------------|-----------|-------|
| Water | 40-50 | 7732-18-5 | Exempt | - | |
| Ethylene Glycol | 50-60 | 107-21-1 203-473-3 | 01-2119456816- 28-XXXX | - | # |
| Sodium 2-ethylhexanoate | <3 | 19766-89-3 243-283-8 | Exempt | - | E |
| Methyl-1H-benzotriazole | <0.5 | 29385-43-1 249-596-6 | 01-2119979081- 35-XXXX | - | |

List of abbreviations and symbols that may be used above:

#: This substance has been assigned Union workplace exposure limit(s).

Composition comments: The full text for all H-statements is displayed in section 16. All concentrations are in percent by weight.

E Exempted from registration as per Annex V of the regulation 1907/2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH).

Section 4: First Aid Measures**General information**

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

4.1. Description of first aid measures

Inhalation: Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact: Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact: Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion: Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed:

Convulsions. Dizziness. Nausea, vomiting. Abdominal pain. Oedema. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed:

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Section 5: Fire Fighting Measures

General fire hazards: No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing media: Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition may produce smoke, oxides of carbon and lower molecular weight organic compounds whose composition have not been characterised.

5.3. Advice for firefighters

Special protective equipment for firefighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire-fighting procedures: Move containers from fire area if you can do so without risk.

Specific methods: Use standard firefighting procedures and consider the hazards of other involved material.

Section 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

For emergency responders: Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Use water spray to reduce vapours or divert vapour cloud drift.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use.

6.4. Reference to other

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

Section 7: Handling and Storage

7.1. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapour. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke.

Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

7.3. Specific end use(s)

Antifreeze / Coolant. Corrosion inhibitor for cooling systems.

Section 8: Exposure Controls / Personal Protection

8.1. Control parameters

| UK. EH40 Workplace Exposure Limits (WELs) | | | |
|---|------|-----------------------|-------------|
| Components | Type | Value | Form |
| Ethylene glycol (CAS 107-21-1) | STEL | 104 mg/g ³ | Vapor |
| | TWA | 40 ppm | Vapor |
| | | 52 mg/g ³ | Vapor |
| | | 10 mg/g ³ | Particulate |

| | | | |
|---|------|---------------------------------|-------|
| | | 20 ppm | Vapor |
| EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU | | | |
| Ethylene glycol (CAS 107-21-1) | STEL | 104 mg/g ³ 40 ppm | |
| | TWA | 52 mg/g ³ 20 ppm | |

Biological limit values: No biological exposure limits noted for the ingredient(s).
Recommended monitoring procedures: Follow standard monitoring procedures.

Derived no effect levels (DNELs)

General Population

| Components | Value | Assessment Factor | Notes |
|--|------------------------|-------------------|-------|
| Ethylene glycol (CAS 107-21-1) | | | |
| Long-term, Local, Inhalation | 7 mg/g ³ | 10 | |
| Long-term, Systemic, Dermal | 53 mg/kg | 84 | |
| Methyl-1H-benzotriazole (CAS 29385-43-1) | | | |
| Long-term, Systemic, Dermal | 0.25 mg/kg | | |
| Long-term, Systemic, Inhalation | 4.25 mg/g ³ | | |
| Long-term, Systemic, Oral | 0.25 mg/kg | | |

Workers

| Components | Value | Assessment Factor | Notes |
|--|-----------------------|-------------------|-------|
| Ethylene glycol (CAS 107-21-1) | | | |
| Long-term, Local, Inhalation | 35 mg/g ³ | 2 | |
| Long-term, Systemic, Dermal | 106 mg/kg | 42 | |
| Methyl-1H-benzotriazole (CAS 29385-43-1) | | | |
| Long-term, Systemic, Dermal | 0.5 mg/kg | | |
| Long-term, Systemic, Inhalation | 8.8 mg/g ³ | | |

Predicted no effect concentrations (PNECs)

| Components | Value | Assessment Factor | Notes |
|--|--------------|-------------------|-------|
| Ethylene glycol (CAS 107-21-1) | | | |
| Freshwater | 10 mg/l | 10 | |
| Intermittent releases | 10 mg/l | 10 | |
| Marine water | 1 mg/l | 100 | |
| Sediment (freshwater) | 37 mg/kg | | |
| Sediment (marine water) | 3.7 mg/kg | | |
| Soil | 1.53 mg/kg | | |
| STP | 199.5 mg/l | 10 | |
| Methyl-1H-benzotriazole (CAS 29385-43-1) | | | |
| Freshwater | 0.008 mg/l | 50 | |
| Intermittent releases | 0.086 mg/l | 100 | |
| Marine water | 0.008 mg/l | 50 | |
| Sediment (freshwater) | 0.0025 mg/kg | 10 | |
| Sediment (marine water) | 0.0025 mg/kg | 10 | |
| Soil | 0.0024 mg/kg | 10 | |
| STP | 39.4 mg/l | 10 | |

Exposure guidelines

UK EH40 WEL: Skin designation

Ethylene glycol (CAS 107-21-1) - Can be absorbed through the skin

8.2. Exposure controls

Appropriate engineering controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment.

General information: Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection: Chemical respirator with organic vapour cartridge and full facepiece.

| | |
|----------------------------------|---|
| Skin protection/Hand protection: | Wear appropriate chemical resistant gloves. Wear suitable gloves tested to EN374. Use gloves classified protection index 6 with breakthrough time of 480 minutes. Minimum glove thickness 0.38 mm. Neoprene, butyl rubber, nitrile or Viton gloves are recommended. Suitable gloves can be recommended by the glove supplier. |
| Other: | Wash hands thoroughly after handling. Use of an impervious apron is recommended. |
| Respiratory protection: | Chemical respirator with organic vapour cartridge and full facepiece. |
| Thermal hazards: | Wear appropriate thermal protective clothing, when necessary. Observe any medical surveillance requirements. |
| Hygiene measures: | Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |
| Environmental exposure controls: | Environmental manager must be informed of all major releases. |

Section 9: Physical and Chemical Properties

| | |
|--|---------------------------|
| Appearance | : Blue Liquid |
| Odour | : Mild |
| Odour Threshold | : NA |
| PH | : 7.8 – 8.8 (20°C) |
| Melting Point/ Freezing Point (°C) | : -36.8 |
| Initial boiling point and range (°C) | : 105-108 |
| Flash Point (°C) [ISO3679, Closed Cup Testing] | : No Flash Point Detected |
| Evaporation Rate | : Not determined |
| Flammability (solid, gas) | : Not applicable |
| Vapour Pressure | : Not determined |
| Upper/lower Flammability (Explosive) Limits | : Not determined |
| Vapour Density | : Not determined |
| Relative Density | : 1.03 – 1.07 kg/l (20°C) |
| Solubility in Water | : Soluble |
| Partition coefficient (N-Octanol/Water) | : Not determined |
| Auto-ignition Temperature (°C) | : Not determined |
| Decomposition Temperature | : Not determined |
| Viscosity (mPa s) | : Not determined |

Section 10: Stability and Reactivity

10.1. Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Material is stable under normal conditions.

10.3. Possibility of hazardous

No dangerous reaction known under conditions of normal use. Reactions

10.4. Conditions to avoid

Contact with incompatible materials.

10.5. Incompatible materials

Strong acids. Strong oxidising agents. Nitrates. Peroxides. Chlorates.

10.6. Hazardous decomposition products

At elevated temperatures: Ketones. Aldehydes.

Section 11: Toxicological Information

General information

Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation

In high concentrations, mists/vapors may irritate throat and respiratory system and cause coughing.

Skin contact

Prolonged or repeated contact may dry skin and cause irritation.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion

Harmful if swallowed. Ingestion of ethylene glycol may result in nausea, vomiting, abdominal cramps, blindness, liver damage, irritation, reproductive effects, nerve damage, convulsions, oedema of the lung, cardiopulmonary effects (metabolic acidosis), pneumonia and kidney failure which could result in death. The single lethal dose for humans is about 100 ml. Inhalation of high levels of vapour or mists for prolonged periods of time may also result in toxic effects.

Symptoms

Convulsions. Dizziness. Nausea, vomiting. Abdominal pain. Oedema.

11.1. Information on toxicological effects

Acute toxicity: Harmful if swallowed.

| Components | Species | Test Result |
|--|-----------------------------|---|
| Ethylene glycol (CAS 107-21-1) Acute Dermal LD50 Inhalation LC50 Oral LD50 | Mouse Rat Cat | > 3500 mg/kg > 2.5 mg/l, 6 Hours 1600 mg/kg |
| Methyl-1H-benzotriazole (CAS 29385-43-1) Acute Dermal LD50 Oral LD50 | Rabbit Rat | > 2000 mg/kg, 24 Hours 720 mg/kg |

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory sensitization

Due to partial or complete lack of data the classification is not possible.

Skin sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

Reproductive toxicity

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure

May cause damage to organs (kidney) through prolonged or repeated exposure.

Aspiration hazard

Due to partial or complete lack of data the classification is not possible.

Mixture versus substance information

No information available.

Other information

No data available.

Section 12: Ecological Information

12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aquatic environment.

| Components | | Species | Test Result |
|--|----------------------|---|---|
| Ethylene glycol (CAS 107-21-1) Aquatic Crustacea | EC50 LC50 | Daphnia magna Fathead minnow (Pimephales promelas) | > 100 mg/l, 48 Hours 72860 mg/l, 96 hours |
| Methyl-1H-benzotriazole (CAS 29385-43-1) Aquatic Acute Algae Crustacea Fish | EC50 LC50 LC50 | Skeletonema costatum Arcartia tonsa Cyprinodon variegatus | 53 mg/l, 72 hours 55 mg/l, 48 hours 55 mg/l, 96 hours |

12.2. Persistence and degradability

Expected to be readily biodegradable.

12.3. Bioaccumulative potential

Partition coefficient

n-octanol/water (log Kow)

Ethylene glycol (CAS 107-21-1): -1.36

Bioconcentration factor (BCF): Not available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects

No data available.

Section 13: Disposal Considerations

13.1. Waste treatment methods

Residual waste

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Disposal methods/information

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of contents/container in accordance with local/regional/national/international regulations.

Special precautions

Dispose in accordance with all applicable regulations.

Section 14: Transport Information

ADR 14.1. - 14.6.:

Not regulated as dangerous goods.

RID 14.1. - 14.6.:

Not regulated as dangerous goods.

ADN 14.1. - 14.6.:

Not regulated as dangerous goods.

IATA 14.1. - 14.6.:

Not regulated as dangerous goods.

IMDG 14.1. - 14.6.:

Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code:

Not established.

Section 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended: Not listed.
- Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended: Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended: Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended: Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended: Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended: Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended: Not listed.
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA: Not listed.

Authorisations

- Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended: Not listed

Restrictions on use

- Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended: Not listed.
- Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended: Not listed.

Other EU regulations

- Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended: Not listed.

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended. All components of this product are compliant with the registration requirements of Regulation (EC) 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals, as amended. All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), IECSC (China), KECl (Korea), PICCS (Philippines), TSCA (United States), TCSI (Taiwan), NZIoC (New Zealand).

National regulations

- Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.
- According to Directive 92/85/EEC as amended, pregnant women should not work with the product, if there is the least risk of exposure.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

Section 16: Other Information

Department Issuing Data Sheet : Central Auto Parts & Equipment Limited
Original Issue Date : 11 August 2021
Revision No. :
Revision Date :

List of abbreviations

TWA: Time weighted average.
STEL: Short term exposure limit.
DNEL: Derived No-Effect Level.
PNEC: Predicted No-Effect Concentration.
STP: Sewage treatment plant.
LD50: Lethal Dose, 50%.

EC50: Effective Concentration, 50%.

LC50: Lethal Concentration, 50%.

PBT: Persistent, bioaccumulative and toxic.

vPvB: Very Persistent and very Bioaccumulative.

References: ECHA CHEM

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

GHS Hazard Statements

Full text of any H-statements not written out in full under Sections 2 to 15

H302 Harmful if swallowed.

H361D Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure by ingestion.

H411 Toxic to aquatic life with long lasting effects.

This data Sheet and the health, safety and environment information it contains is considered to be accurate as of the data specified below. We have reviewed any information contained herein which we received from sources outside the company. However, no warranty or representation, express or implied is made as to the accuracy or completeness of the data and information contained in this data sheet. Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as a permission, recommendation or authorization given or implied to practise any patented invention without a valid licence. Central Auto Parts and Equipment Limited shall not be responsible for any damage or injury resulting from abnormal use of the material, from any failure adhere to recommendations, or from any hazards inherent in the nature of the material.