



GIANT MTF 75W

Fully Synthetic Manual Transmission Fluid

DESCRIPTION

GIANT MTF 75W is a multi-vehicle manual transmission fluid (MTF), based on high-quality fully synthetic base oils in combination with advanced additives formulated for manual transmissions and modern dry clutch transmissions (DCT).

PERFORMANCE STANDARDS

- API GL-4
- Ford WSD-M2C200-C/WSS-M2C200-D2/ESD-M2C186-A
- Honda MTF / MTF-II / MTF-III
- PSA B71 2310 / 2315 / 2316 / 2330
- Tranself NFJ/NFP/NFX/TRJ/TRP/TRT/TRX/TRZ
- VW G 052 527 / 052 549 / 052 726
- BMW MTF LT-2 / LT-3 / LT-4
- GM GMW16612/1940004/19259104
- MB 235.10
- Renault DC4 / DW5
- Volvo 97308 / 97309
- VW G 50 / 055 512 / 060 726 / 070 726
- Fiat 9.55550-MZ1 / MZ6 / MZ7
- GM 1940182/1940764/1940768
- Nissan MT-XZ / MT-XZ TL (JR Type)
- Special gear oil, MTF 94
- VW G 009 317 / 052 171 / 052 178 / 052 512

TYPICAL APPLICATIONS

GIANT MTF 75W has been specially developed for European and Asian vehicles (passenger cars and delivery vans), where the specified specifications are requested. This oil is also suitable for manual transmissions and mechanical gearboxes where specifications are prescribed in combination with slightly different viscosities, such as 70W75, 70W90, 75W, 75W85 75W90 etc.

This product may also be used in selected models of semi-automatic, differential/reduction gear units found in Hybrid (HEV), Plug-in Hybrids (PHEV) and full Electric Vehicles (EV).

BENEFITS

- proven performance in European and Asian synchronisers
- superior bearing and gear protection
- excellent cleanliness
- good low temperature performance
- robust corrosion protection
- long durability with very high-quality EP-properties

TYPICAL PROPERTIES

SAE Grade	75W
Density, kg/Litre @ 15°C	0.854
Kinematic Viscosity, mm ² /s @ 40°C	32.5
Kinematic Viscosity, mm ² /s @ 100°C	6.3
Viscosity Index	148
Pour Point, °C	-42
Flash Point COC, °C	210